



WATCH IT IN ACTION
GUARDA IN AZIONE

TE9DF2

TRINCIA PER ESCAVATORE HYDRAULIC MULCHER



Trincia per escavatore CARATTERISTICHE

- Potente trincia forestale con una notevole capacità di taglio, progettata per arbusti e piante.
- Trasmissione a cinghie trapezoidali dentate.
- Telaio privo di sportello per una maggiore capacità di taglio.
- Rotore a denti fissi con dente a doppia lama e limitatore di mordente.
- Supporti rotore interni per la protezione dei cuscinetti dalle impurità.
- Protezione carter cinghie.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Cuscinetti rotore a doppia corona di rulli orientabili.
- Motore gruppo 3 in ghisa.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

Hydraulic mulcher FEATURES

- Powerful forestry mulcher designed for clearing shrubs and plants with increased cutting capacity.
- Toothed high-performance belts transmission.
- Body without hoods for increased cutting capacity.
- Fixed-tooth rotor with double-bladed tool and bite limiter.
- Inside rotor supports for the protection of the bearings from the impurities.
- Protective belts cover.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and auto-draining.
- Double row ball bearings.
- Cast iron gear motor group 3.

Upon request:

- mounting bracket, custom-made available;
- hoses.

DATI TECNICI

DATA SHEET



TE9DF2



TE9SPDF2



DFD Rotore Rotor



DFHF22
 MAX 200 mm

							CILINDRATA MOTORE ENGINE DISPLACEMENT	
TE1.9-70DF2 TE1.9-70SPDF2	5 - 12 tons	70 mm 28"	85x65x64 cm 34x25x24 inch	345 kg 760 lbs	200-220 bar 2900-3200 psi	40-100 l/min 14-28 gpm	40-50-60- 80-100 cc	14
TE2.9-90DF2 TE2.9-90SPDF2	6 - 12 tons	90 mm 36"	105x65x64 cm 42x25x24 inch	400 kg 882 lbs	200-220 bar 2900-3200 psi	50-100 l/min 14-28 gpm	50-60- 80-100 cc	18
TE2.9-110DF2 TE2.9-110SPDF2	6 - 12 tons	110 mm 44"	124x65x64 cm 49x25x24 inch	470 kg 1036 lbs	200-220 bar 2900-3200 psi	50-100 l/min 14-28 gpm	50-60- 80-100 cc	22

Gamma di motori idraulici a ingranaggi disponibili
Hydraulic gear motor range available

	5-6 ton	6-7 ton	7-8 ton	8-10 ton	10-12 ton
CILINDRATA MOTORE ENGINE DISPLACEMENT	22 cc	27 cc	34 cc	43 cc	51 cc
	40 l/min 11 gpm	50 l/min 14 gpm	60 l/min 16 gpm	80 l/min 22 gpm	100 l/min 28 gpm

TE9DF2 | TRINCIA PER ESCAVATORE - HYDRAULIC MULCHER