



WATCH IT IN ACTION
GUARDA IN AZIONE

TE3

TRINCIA PER ESCAVATORE HYDRAULIC MULCHER



Trincia per escavatore

CARATTERISTICHE

- Trinciatrice progettata per la pulizia di erba e arbusti.
- Rullo di appoggio regolabile su 3 posizioni per variare l'altezza di taglio
- Rotore elicoidale con mazze bonificate o coltelli intercambiabili.
- Protezione carter motore.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore gruppo 2 in alluminio.
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

Hydraulic mulcher

FEATURES

- Mulcher designed for cleaning grass and shrubs.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with tempered hammers or interchangeable blades.
- Protective cover for motor.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- Aluminium group 2 gear motor.
- Accident prevention rubber protections according to EC directives

Upon request:

- mounting bracket, custom-made available;
- hoses.

DATI TECNICI
DATA SHEET



K/M Rotore
 Rotor



MAZHF2
 MAX 50 mm

CLTKF1
 MAX 30 mm

			LxAxH	KG	min - max	min - max	CILINDRATA MOTORE ENGINE DISPLACEMENT	
TE1.3-70K/M	1,5 - 5 tons	70 mm 28"	95x55x45 cm 38x22x18 inch	130 kg 287 lbs	170-220 bar 2500-3200 psi	20-40 l/min 6-11 gpm	8-11-16 cc	10
TE2.3-90K/M	2 - 5 tons	90 mm 36"	115x55x45 cm 46x22x18 inch	150 kg 331 lbs	170-220 bar 2500-3200 psi	30-40 l/min 8-11 gpm	11-16 cc	14

Gamma di motori idraulici a ingranaggi disponibili
 Hydraulic gear motor range available

	1,5-2 ton	2-3,5 ton	3,5-5 ton
CILINDRATA MOTORE ENGINE DISPLACEMENT	8 cc	11 cc	16 cc
OIL	20 l/min 6 gpm	30 l/min 8 gpm	40 l/min 11 gpm