



WATCH IT IN ACTION  
GUARDA IN AZIONE

# TESK10

## TRINCIA PER MINI PALA HYDRAULIC MULCHER



### Trincia per mini pala

#### CARATTERISTICHE

- Potente trinciatrice forestale, progettata per il montaggio su minipala.
- Attacco fisso universale.
- Rotore DF a denti fissi in widia o lama o bonificata.
- Traslazione idraulica.
- Abbattirami meccanico.
- Manometro per controllo pressione di lavoro.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione.
- Motore a pistoni a cilindrata fissa.
- Protezioni antinfortunistiche in gomma a norma CE.

#### Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

### Hydraulic mulcher

#### FEATURES

- Powerful forestry mulcher, designed for mounting on skid steer loaders.
- Fixed universal hitch.
- DF forestal rotor with fixed teeth.
- Hydraulic translation.
- Mechanically adjustable push bar.
- Manometer for working pressure control.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve) and anti-cavitation.
- Piston motor.
- Accident prevention rubber protections according to EC directives.

#### Upon request:

- mounting bracket, custom-made available;
- hoses.

**DATI TECNICI**  
**DATA SHEET**



**DF** Rotore  
 Rotor



DFHF14P  
 MAX 300 mm

DFHF15  
 MAX 250 mm

							CILINDRATA MOTORE ENGINE DISPLACEMENT	
			LxAxH	KG	min - max	min - max		
TESK1.10-160DF	70 - 120 hp	160 mm 63"	200x100x160 cm 79x40x63 inch	1285 kg 2833 lbs	200-350 bar 2900-5100 psi	100-180 l/min 28-48 gpm	45-60-80 cc	42
TESK1.10-180DF	70 - 120 hp	180 mm 71"	220x100x160 cm 87x40x63 inch	1420 kg 3131 lbs	200-350 bar 2900-5100 psi	100-180 l/min 7-9 gpm	45-60-80 cc	54

Gamma di motori idraulici a pistoni disponibili

Hydraulic piston motor range available

CILINDRATA MOTORE ENGINE DISPLACEMENT	45 cc	60 cc	80 cc
	100 l/min 28 gpm	130 l/min 35 gpm	180 l/min 48 gpm