

TE GAMMA TRINCE PER ESCAVATORE EXCAVATOR MULCHER RANGE



TE

GAMMA TRINCE PER ESCAVATORE EXCAVATOR MULCHER RANGE

	TE1	TE3	TE4	TE7	TE9	TE9-2	TE13	TE15	TE20
									
	1 - 3 tons	1,5 - 5 tons	1 - 3 tons	5 - 8 tons	3 - 12 tons	5 - 12 tons	8 - 16 tons	12 - 25 tons	16 - 30 tons
 MAX	Ø max 3 cm Ø max 1,18"	Ø max 5 cm Ø max 1,96"	Ø max 12 cm Ø max 4,72"	Ø max 8 cm Ø max 3,15"	Ø max 25 cm Ø max 9,85"	Ø max 20 cm Ø max 7,87"	Ø max 25 cm Ø max 9,85"	Ø max 25 cm Ø max 9,85"	Ø max 30 cm Ø max 11,8"
 min - max	20-30 l/min 6-8 gpm	20-30-40 l/min 6-8-11 gpm	35-45-55 l/min 9-12-15 gpm	60-70-80 l/min 16-19-22 gpm	40-50-60 l/min 80-100 11-14-16 gpm 22-28	40-50-60 l/min 80-100 11-14-16 gpm 22-28	80-90 l/min 22-28 gpm	90-180 l/min 25-50 gpm	100-130-180 l/min 28-35-48 gpm
 min - max	170-220 bar 2500-3200 psi	170-220 bar 2500-3200 psi	180-250 bar 2500-3200 psi	200-220 bar 2900-3200 psi	170-220 bar 2500-3200 psi	200-220 bar 2900-3200 psi	200-220 bar 2900-3200 psi	200-250 bar 2900-3600 psi	200-350 bar 2900-5100 psi
CILINDRATA MOTORE ENGINE DISPLACEMENT	8 - 11 cc	8 - 11 - 16 cc	12 - 16 - 20 cc	22 - 27 - 34 cc	22-27-34-cc 44-51	22-27-34-cc 44-51	43 - 51 cc	32 - 64 cc	45 - 60 - 80 cc
	direct diretta	direct diretta	direct diretta	direct diretta	3	3	1 (50mm)	1 (50 mm)	1 (50 mm)
ROTORE FORESTALE FORESTRY ROTOR	—	—	✓	—	✓	✓	✓	✓	✓