

GS

GAMMA PINZE MOTOSEGA GRAPPLE SAWS RANGE

	GS250	GS400	GS600	GS800
				
	3 - 6 tons	5 - 10 tons	12 - 22 tons	22 - 30 tons
	230 kg 510 lbs	410 kg 904 lbs	860 kg 1896 lbs	1650 kg 3638 lbs
	250 mm 9.9"	400 mm 16"	600 mm	800 mm
CARICO MASSIMO/ MAXIMUM WORKLOAD	400 kg 880 lbs	1500 kg 3305 lbs	2200 kg 4850 lbs	3000 kg 6614 lbs
APERTURA MASSIMA/ MAXIMUM OPENING	430 mm 16.9"	950 mm 35.5"	1450 mm 57"	2200 mm 87"
	220 - 250 bar 3190 - 3625 psi	220 - 250 bar 3190 - 3625 psi	PINZA + SEGA GRAPPLE + SAW ROTAZIONE ROTATION	PINZA + SEGA GRAPPLE + SAW ROTAZIONE ROTATION
min - max			250 bar 3625 psi 180 bar 2610psi	250 bar 3625 psi 200 bar 2900 psi
	15 - 50 l/min 4 - 13 gpm	30 - 60 l/min 8 - 16 gpm	PINZA + SEGA GRAPPLE + SAW ROTAZIONE ROTATION	PINZA + SEGA GRAPPLE + SAW ROTAZIONE ROTATION
min - max			100 l/min 26 gpm 40 l/min 11 gpm	160 l/min 42 gpm 70 l/min 18 gpm
	Motore a pistoncini "Parker" 6 cc "Parker" piston motor 6 cc	Motore a pistoncini "Parker" 6 cc "Parker" piston motor 6 cc	Motore a pistoncini "Parker" 10 cc "Parker" piston motor 10 cc	Motore a pistoncini "Parker" 30 cc "Parker" piston motor 30 cc
CATENA SAW CHAIN	.404" 1,6 mm	.404" 1,6 mm	.404"	3/4"
	400 mm 15,8"	550 mm 21,6"	750 mm 29"	1050 mm 41"
	360°	360°	360°	360°