


TE

GAMMA TRINCE MULCHER RANGE

	TE1	TE3	TE7	TE9	TE9DF2	TE13	TE15	TE20	TESK5	TESK10
										
	1 - 3 tons	1,5 - 5 tons	5 - 8 tons	3 - 12 tons	5 - 12 tons	8 - 16 tons	12 - 25 tons	16 - 30 tons		
									50 - 90 hp	70 - 120 hp
 MAX	Ø max 3 cm Ø max 1,18"	Ø max 5 cm Ø max 1,96"	Ø max 8 cm Ø max 3,15"	Ø max 25 cm Ø max 9,85"	Ø max 20 cm Ø max 7,87"	Ø max 25 cm Ø max 9,85"	Ø max 25 cm Ø max 9,85"	Ø max 30 cm Ø max 11,8"	Ø max 8 cm Ø max 3,15"	Ø max 30 cm Ø max 11,8"
 min - max	20-30 bar 6-8 psi	20-30-40 bar 6-8-11 psi	60-70-80 bar 16-19-22 psi	40-50-60- 80-100 bar 11-14-16- 22-28 psi	40-50-60- 80-100 bar 11-14-16- 22-28 psi	80-90 bar 22-28 psi	90-180 bar 25-50 psi	100-130- 180 bar 28-35-48 psi	60-70- 90-100 bar 16-22- 24-28 psi	100-130-180 bar 28-35-48 psi
 min - max	170-220 l/min 2500-3200 gpm	170-220 l/min 2500-3200gpm	200-220 l/min 2900-3200 gpm	170-220 l/min 2500-3200 gpm	200-220 l/min 2900-3200 gpm	200-220 l/min 2900-3200 gpm	200-250 l/min 2900-3600 gpm	200-350 l/min 2900-5100 gpm	200-220 l/min 2900-3200 gpm	200-350 l/min 2900-5100 gpm
CILINDRATA MOTORE ENGINE DISPLACEMENT	8 - 11 cc	8 - 11 - 16 cc	22 - 27 - 34 cc	22-27-34-cc 44-51	22-27-34- cc 44-51	43 - 51 cc	32 - 64 cc	45 - 60 -80 cc	27-34- 43-51 cc	45-60-80 cc
	direct diretta	direct diretta	direct diretta	3	3	1 (50mm)	1 (50 mm)	1 (50 mm)	4	1