



WATCH IT IN ACTION
GUARDA IN AZIONE

TESK1

TRINCIA PER MINI PALA HYDRAULIC MULCHER



Trincia per mini pala

CARATTERISTICHE

- Trinciatrice compatta, progettata per il montaggio su mini pala cingolata.
- Rotore elicoidale K/M con mazze bonificate.
- Corpo interno a doppia cassa con intercapedine.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Cuscinetti di alta qualità.
- Motore a ingranaggi in ghisa.
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

Hydraulic mulcher

FEATURES

- Compact mulcher, designed for mounting on mini track loaders.
- K/M helicoidal rotor with austempered hammers.
- High-performance V-belts transmission.
- Internally reinforced double-case body.
- Valves block completely using a priority valve for adjusting the oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- Bearings of first quality.
- Cast iron gear motor.
- Accident prevention rubber protections according to EC directives.

Upon request:

- mounting bracket, custom-made available;
- hoses.

DATI TECNICI
DATA SHEET



K/M Rotore
 Rotor



MAZHF2
 MAX 50 mm

| | | | | | | | CILINDRATA MOTORE ENGINE DISPLACEMENT | |
|----------------|------------|---------------|-------------------------------|-------------------|------------------------------|--------------------------|---|----|
| | | | LxAxH | kg | min - max | min - max | | |
| TESK1.1-120K/M | 50 - 90 hp | 120 cm 47" | 134x67x54 cm 53x26x22 inch | 200 kg 441 lbs | 170-220 bar 2500-3200 psi | 40-60 l/min 11-16 gpm | 22-27-34 cc | 20 |
| TESK2.1-140K/M | 50 - 90 hp | 140 cm 55" | 154x67x54 cm 61x26x22 inch | 220 kg 485 lbs | 170-220 bar 2500-3200 psi | 40-60 l/min 11-16 gpm | 22-27-34 cc | 24 |
| TESK3.1-160K/M | 50 - 90 hp | 160 cm 62" | 174x67x54 cm 69x26x22 inch | 240 kg 529 lbs | 170-220 bar 2500-3200 psi | 40-60 l/min 11-16 gpm | 22-27-34 cc | 28 |

Gamma di motori idraulici a ingranaggi disponibili
 Hydraulic motor range available

| CILINDRATA MOTORE ENGINE DISPLACEMENT | 22 cc | 27 cc | 34 cc |
|---|--------------------|--------------------|--------------------|
| | 40 l/min 11 gpm | 50 l/min 13 gpm | 60 l/min 16 gpm |